



**PCIe-S144i**

PCI Express, Serial Communication Board with  
4 Isolated RS-422/485 ports

### Features

- Supports PCI Express x1
- Provides 4 RS-422/485 ports
- 256-byte Hardware FIFO for Each Port
- Transmission Speed of up to 921600 bps
- 256 modules max. in one RS-485 network
- Automatic RS-485 direction control
- ±4 kV ESD Protection for i versions
- 3000 VDC Isolation for i versions
- Short Card Design



### Hardware Specifications

Models	PCIe-S144i
<b>Hardware</b>	
Connector	DB-37 (Female)
<b>COM Ports</b>	
Ports	4 x RS-422/485 (RS-422: TxD+, TxD-, RxD+, RxD-, RTS+, RTS-, CTS+, CTS-, GND / RS-485: Data+, Data-, GND)
Baud Rate	300 - 921600 bps
Parity	None, Even, Odd, Mark, Space
Data Bit	5, 6, 7, 8
Stop Bit	1, 1.5, 2
FIFO Size	Internal 256 bytes
Isolation	3000 VDC
<b>Power</b>	
Consumption	440 mA @ 5 V
<b>Mechanical</b>	
Dimensions (mm)	101 x 114 x 22 (W x L x D)
<b>Environmental</b>	
Operating Temperature	0 ~ +60°C
Storage Temperature	-20 ~ 70°C
Humidity	5 ~ 85% RH, Non-condensing

### Accessories

<p>DN-37-381 CR</p>	Female DB37 to Screw Terminal Board (Pitch= 3.81 mm) with DIN-rail Mounting (RoHS) Include: CA-3710 (DB37 Male to Male, 45°, 1M)
<p>CA-9-3715D CR</p>	Male DB-37 to 4-port Male DB-9 Cable, 1.5 M (180°)
<p>CA-9-3705 CR</p>	Male DB-37 to 4-port Male DB-9 Cable, 0.3 M (90°)

### Software

#### Drivers

- 32-bit and 64-bit Windows XP/2003/2008/7/8/10
- Linux

### Pin Assignments

Pin Assignment	Terminal No.	Pin Assignment
N.C.	01	20 CTS3-(A)
TxD3-(A)/Data3-(A)	02	21 RxD3-(A)
GND	03	22 RTS3-(A)
CTS3+(B)	04	23 RTS3+(B)
TxD3+(B)/ata3+(B)	05	24 RxD3+(B)
CTS4-(A)	06	25 TxD4-(A)/Data4-(A)
RxD4-(A)	07	26 GND
RTS4-(A)	08	27 CTS4+(B)
RTS4+(B)	09	28 TxD4+(B)/Data+(B)
RxD4+(B)	10	29 CTS2-(A)
TxD2-(A)/Data2-(A)	11	30 RxD2-(A)
GND	12	31 RTS2-(A)
CTS2+(B)	13	32 RTS2+(B)
TxD2+(B)/Data2+(B)	14	33 RxD2+(B)
CTS1-(A)	15	34 TxD1-(A)/Data1-(A)
RxD1-(A)	16	35 GND
RTS1-(A)	17	36 CTS1+(B)
RTS1+(B)	18	37 TxD1+(B)/Data1+(B)
RxD1+(B)	19	

RS-422/485 Female DB-37 Connector

Pin Assignment	Terminal No.	Pin Assignment
GND	05	09 CTS-(A)
RxD-(A)	04	08 CTS+(B)
RxD+(B)	03	07 RTS+(B)
TxD+(B)/Data+(B)	02	06 RTS-(A)
TxD-(A)/Data-(A)	01	

RS-422/485 Female DB-37 to Male DB-9 Connector

### Ordering Information

<b>PCIe-S144i CR</b>	PCI Express, Serial Communication Board with 4 Isolated RS-422/485 ports (RoHS)
----------------------	---